

































- Li X, Quadrifoglio L (2009) Optimal zone design for feeder transit services. *Transp Res Rec* 2111(2):100–108
- Li X, Quadrifoglio L (2010) Feeder transit services: choosing between fixed or demand responsive policy. *Transp Res Part C, Emerg Technol* 18, 770–780
- Quadrifoglio L, Li X (2009) A methodology to derive the critical demand density for designing and operating feeder transit services. *Transp Res, Part B* 43:922–935
- Quadrifoglio L, Li X (2008) Performance assessment and comparison between fixed and flexible transit services for different urban settings and demand distributions. Report No SWUTC/08/473700-00090-1, Texas Transportation Institute, 2008. <http://swutc.tamu.edu/publications/technicalreports/473700-00090-1.pdf>, accessed on Oct 5, 2010
- Quadrifoglio L, Dessouky MM, Palmer K (2007) An insertion heuristic for scheduling mobility allowance shuttle transit (MAST) services. *J Sched* 10(1):25–40
- Quadrifoglio L, Hall RW, Dessouky MM (2006) Performance and design of mobility allowance shuttle transit services: bounds on the maximum longitudinal velocity. *Transp Sci* 40(3):351–363
- Quadrifoglio L, Dessouky MM, Ordóñez F (2008a) Mobility allowance shuttle transit (MAST) services: MIP formulation and strengthening with logic constraints. *Eur J Oper Res* 185(2):481–494
- Quadrifoglio L, Dessouky MM, Ordóñez F (2008b) A simulation study of demand responsive transit system design. *Transp Res, Part A* 42(4):718–737
- Sandlin AB, Anderson MD (2004) Serviceability index to evaluate rural demand-responsive transit system operations. *Transp Res Rec* 1887:205–212
- Savelsbergh MWP, Sol M (1995) The general pickup and delivery problem. *Transp Sci* 29(1):1–20
- Texas Transportation Institute (1996) Guideline for the location and design of bus stops. TTI Report 19. Transportation Research Board, Washington DC
- Yim YB, Ceder A (2006) Smart feeder/shuttle bus service: consumer research and design. *J Publ Transp* 9(2):97–121